

NOTE:

- 1. CABLE: 30AWG,UL1007.WIRE CABLE*10PCS.
- 2. LENGHT: 30mm*10PCS.
- 3. CONNECTOR: USB3.0(A)M*1PC; USB3.0 MICRO10P(B)M *1PC(BLUE INSULATION)(SHELL GOLD PLATED).
- 4. NOTE: CONTACTS:

USB3.0(A)M	1	2	3	4	5	6	7	8	9	64
MIRCO USB BM 10PIN	1	2	3	5	6	7	8	9	10	64
MOLDIMOLDING TYPE										SHFLL

5. MOLD: MOLDING TYPE.

6. Test machine test condition.

A.100% OPEN, SHORT&INTERMITANCE TEST.

B.CONDUCTOR RESISTANCE: 30hms MAX:

C.INSULATION RESISTANCE: 5M Min/,10ms:

7. ALL MUST BE MEET ON ROHS COMPLIANT.

Pantone 2945C, Black 材質: 80P銅版紙,上亮PP(光膠) Label Size: 50 x 35 mm R= 2mm



PACKING: 1PCS/PE BAG+LABEL(4052792001532), 50PCS/BIG BAG.

L	COMPANY			ITEM NO.	AU0024	NO				
	REVISI□N	DATE	DISCRIPTION	DRAWN RY					SCALE	NDN
	REV.A/0	2012.02.24	C14-1202003	DESTUNCE USBS.0 A Ivide - USBS.0 I Ivide			2direct GmbH	UNIT(mm)		
L				BY APPROVAL		Gold Flash Shell				
				BY					PAGE	1/1