



PACKING: Guest box + LABEL.

NOTE:

1. CABLE: 32AWG, UL20276, AL+D-FOLL, [(#32*1P+D+FAM)*5PCS+#32*4C], WHITE COLOR, OD=3.8±0.2mm, PVC JACKET*1PC.
2. LENGTH: L.
3. CONNECTORS: HDMI19P(M)*2PCS(BLACK INSULATOR)(SHELL GOLD PLATED).
4. MOLD: ASS'Y Iphone TYPE.
5. CONTACTS:

HDMI(M)	1	3	2	4	6	5	7	9	8	10	12	11	14	19	17	13	15	16	18	18	64
HDMI(M)	1	3	2	4	6	5	7	9	8	10	12	11	14	19	17	13	15	16	18	18	64
	PAIR		PAIR		PAIR		PAIR		PAIR		PAIR		PAIR		PAIR		PAIR		PAIR		SHELL
6. Test machine test condition.
 - A. 100% OPEN, SHORT & INTERMITTANCE TEST.
 - B. CONDUCTOR RESISTANCE: 30ohms MAX.
 - C. INSULATION RESISTANCE: 5M Min / 10ms.
7. ALL MUST BE MEET ON ROHS COMPLIANT.

COMPANY	2D		ITEM NO.	CH0040W	NO	B6019	Part Name	HDMI M-MICRO HDMI APPLE HDMI REV1.4
REVISION	DATE	DISCRPTION	DRAWN BY		spec			
REV.A/0	2011.12.15	T6-1112013	DESIGNED BY					
			APPROVAL BY					
SCALE		2direct GmbH						
UNIT(mm)		PAGE						
1/1		1/1						